

DUCTED SPLIT MDB- B SERIES

COOLING ONLY MODEL		INDOOR UNIT		MDB075B	MDB100B	MDB125C	MDB150B2	MDB200B2	
		OUTDOOR UNIT		MMC075C	MMC100B	MMC125B	MMC075C x 2	MMC100B x 2	MMC100C x 2
NOMINAL COOLING CAPACITY			Btu/h	74,000	98,800	116,000	148,000	200,000	200,000
			W	21,688	28,957	33,998	43,376	58,600	58,600
POWER SOURCE			V/Ph/Hz	380~415 / 3 / 50	380~415 / 3 / 50	380~415 / 3 / 50	380~415 / 3 / 50	380~415 / 3 / 50	380~415 / 3 / 50
INDOOR UNIT	UNIT DIMENSION	HEIGHT	mm/in	572 / 22.51	572 / 22.51	736 / 28.97	885 / 34.84	945 / 37.20	
		WIDTH	mm/in	1502 / 59.13	1502 / 59.13	1640 / 64.56	1640 / 65.54	1894 / 74.56	
		DEPTH	mm/in	761 / 29.96	761 / 29.96	965 / 37.99	1040 / 40.94	980 / 38.58	
OUTDOOR UNIT	UNIT DIMENSION	HEIGHT	mm/in	946 / 37.24	946 / 37.24	946 / 37.24	946 / 37.24	946 / 37.24	971.4 / 38.24
		WIDTH	mm/in	1300 / 51.18	1116 / 43.93	1116 / 43.93	1300 / 51.18	1116 / 43.93	1393 / 54.84
		DEPTH	mm/in	500 / 19.68	939 / 36.96	939 / 36.96	500 / 19.68	939 / 36.96	500 / 19.68

DUCTED SPLIT MDB- B SERIES

COOLING ONLY MODEL		INDOOR UNIT		MDB250B2	MDB300B2	MDB300B3		MDB350B3	
		OUTDOOR UNIT		MMC125B x 2	MMC150C x 2	MMC100B x 3	MMC100C x 3	AMC100B x 1	AMC125B x 2
NOMINAL COOLING CAPACITY			Btu/h	250,000	300,000	300,000	300,000	350,000	
			W	73,250	87,900	87,900	87,900	102,550	
POWER SOURCE			V/Ph/Hz	380~415 / 3 / 50		380~415 / 3 / 50		380~415 / 3 / 50	
INDOOR UNIT	UNIT DIMENSION	HEIGHT	mm/in	1291 / 50.82		1291 / 50.82		1546 / 60.86	
		WIDTH	mm/in	1866 / 73.46		1866 / 73.46		2122 / 83.54	
		DEPTH	mm/in	1199 / 47.20		1199 / 47.20		1199 / 47.20	
OUTDOOR UNIT	UNIT DIMENSION	HEIGHT	mm/in	946 / 37.24	1041 / 40.98	946 / 37.24	971.4 / 38.24	946 / 37.24	
		WIDTH	mm/in	1116 / 43.93	1116 / 43.93	1116 / 43.93	1393 / 54.84	1116 / 43.93	
		DEPTH	mm/in	939 / 36.96	939 / 36.96	939 / 36.96	500 / 19.68	939 / 36.96	

DUCTED SPLIT MDB-B SERIES

COOLING ONLY MODEL		INDOOR UNIT	MDB400B4		MDB450B3	MDB500B4	MDB600B4	MDB750B5
		OUTDOOR UNIT	AMC100B x 4	AMC100C x 4	AMC150C x 3	AMC125B x 4	AMC150C x 4	AMC150C x 5
NOMINAL CAPACITY		Btu/h	400,000	400,000	450,000	500,000	600,000	750,000
		W	117,200	117,200	131,850	146,500	175,800	219,750
POWER SOURCE		V/Ph/Hz	380~415 / 3 / 50		380~415 / 3 / 50		380~415 / 3 / 50	
INDOOR UNIT	UNIT DIMENSION	HEIGHT	mm/in	1546 / 60.86	1546 / 60.86	1546 / 60.86	1977.8 / 77.86	2257 / 88.85
		WIDTH	mm/in	2274 / 89.52	2274 / 89.52	2274 / 89.52	2274 / 89.52	2274 / 89.52
		DEPTH	mm/in	1466 / 57.71	1466 / 57.71	1466 / 57.71	1905 / 75.00	1905 / 75.00
OUTDOOR UNIT	UNIT DIMENSION	HEIGHT	mm/in	946 / 37.24	971.4 / 38.24	1041 / 40.98	946 / 37.24	1041 / 40.98
		WIDTH	mm/in	1116 / 43.93	1393 / 54.84	1116 / 43.93	1116 / 43.93	1116 / 43.93
		DEPTH	mm/in	939 / 36.96	500 / 19.68	939 / 36.96	939 / 36.96	939 / 36.96

DUCTED SPLIT MDB-D SERIES

COOLING ONLY MODEL		INDOOR UNIT		MDB075D	MDB100D	MDB125D	MDB125D2	MDB150D1	MDB150D2
		OUTDOOR UNIT		AMC075D	AMC100D	MMC125D	MLC061C x 2	MMC150D	MMC75D x 2
NOMINAL CAPACITY			Btu/h	75,000	100,000	125,000	117,000	150,000	150,000
			W	21,975	29,300	36,625	34,281	43,950	43,950
POWER SOURCE			V/Ph/Hz	380~415 / 3 / 50			380~415 / 3 / 50		380~415 / 3 / 50
INDOOR UNIT	UNIT DIMENSION	HEIGHT	mm/in	507 / 19.96	507 / 19.96	710 / 27.95	710 / 27.95	710 / 27.95	710 / 27.95
		WIDTH	mm/in	1507 / 59.33	1917.2 / 75.48	1794 / 70.63	1794 / 70.63	2073 / 81.61	2073 / 81.61
		DEPTH	mm/in	904 / 35.59	904 / 35.59	1008.8 / 39.71	1013.8 / 39.91	1008.8 / 39.71	1013.8 / 39.91
OUTDOOR UNIT	UNIT DIMENSION	HEIGHT	mm/in	1040.5 / 40.96		1141.6 / 44.94	850 / 33.46	1141.6 / 44.94	1040.5 / 40.96
		WIDTH	mm/in	981 / 38.62		1083 / 42.63	1115 / 43.89	1083 / 42.63	981 / 38.62
		DEPTH	mm/in	981 / 38.62		1083 / 42.63	528 / 20.78	1083 / 42.63	981 / 38.62

DUCTED SPLIT MDB-D SERIES

COOLING ONLY MODEL		INDOOR UNIT		MDB200D2		MDB250D2	
		OUTDOOR UNIT		MMC100D x 2	MMC200D2	MMC125D x 2	MMC250D2
NOMINAL CAPACITY			Btu/h	200,000	200,000	250,000	250,000
			W	58,600	58,600	73,250	73,250
POWER SOURCE			V/Ph/Hz	380~415 / 3 / 50		380~415 / 3 / 50	
INDOOR UNIT	UNIT DIMENSION	HEIGHT	mm/in	880.6 / 34.66		982.2 / 38.66	
		WIDTH	mm/in	1324 / 52.12		1486 / 58.50	
		DEPTH	mm/in	1259.8 / 49.59		1348.7 / 53.09	
OUTDOOR UNIT	UNIT DIMENSION	HEIGHT	mm/in	1040.5 / 40.96	1235.4 / 48.63	1141.6 / 44.94	1433.1 / 56.42
		WIDTH	mm/in	981 / 38.62	2292 / 90.23	1083 / 42.63	2292 / 90.23
		DEPTH	mm/in	981 / 38.62	1158.5 / 45.61	1083 / 42.63	1158.5 / 45.61

DUCTED SPLIT MDB-D SERIES

COOLING ONLY MODEL		INDOOR UNIT		MDB300D2		MDB400D4		MDB500D4		
		OUTDOOR UNIT		MMC150D x 2	MMC300D2	MMC100D x 4		MMC125D x 4		
NOMINAL CAPACITY		Btu/h	300,000		300,000		400,000		500,000	
		W	87,920		87,920		117,200		146,500	
POWER SOURCE		V/Ph/Hz	380~415 / 3 / 50		380~415 / 3 / 50		380~415 / 3 / 50		380~415 / 3 / 50	
INDOOR UNIT	UNIT DIMENSION	HEIGHT	mm/in	982.2 / 38.66		1175.2 / 46.26		1175.2 / 46.26		
		WIDTH	mm/in	1486 / 58.50		1722 / 67.79		1722 / 67.79		
		DEPTH	mm/in	1551.9 / 61.09		1742.4 / 68.59		2098 / 82.59		
OUTDOOR UNIT	UNIT DIMENSION	HEIGHT	mm/in	1141.6 / 44.94	1433.1 / 56.42	1040.5 / 40.96		1141.6 / 44.94		
		WIDTH	mm/in	1083 / 42.63	2292 / 90.23	981 / 38.62		1083 / 42.63		
		DEPTH	mm/in	1083 / 42.63	1158.5 / 45.61	981 / 38.62		1083 / 42.63		

DUCTED SPLIT MDB- BR SERIES

HEATPUMP MODEL		INDOOR UNIT		MDB075BR	MDB100BR	MDB125CR	MDB150BR2	MDB200BR2	MDB250BR2
		OUTDOOR UNIT		MMC075CR	MMC100BR	MMC125BR	MMC075CR x 2	MMC100BR x 2	MMC125BR x 2
NOMINAL COOLING CAPACITY		Btu/h		74,000	98,800	116,000	148,000	197,600	232,000
		W		21,688	28,957	33,998	43,376	57,913	67,995
NOMINAL HEATING CAPACITY		Btu/h		74,000	96,500	120,000	148,000	193,000	240,000
		W		21,688	28,283	35,170	43,376	56,565	70,340
POWER SOURCE		V/Ph/Hz		380~415 / 3 / 50			380~415 / 3 / 50		
INDOOR UNIT	UNIT DIMENSION	HEIGHT	mm/in	572 / 22.51		736 / 28.97	885 / 34.84	885 / 34.84	1231 / 48.46
		WIDTH	mm/in	1502 / 59.13		1640 / 64.56	1640 / 65.54	1894 / 74.56	1866 / 73.46
		DEPTH	mm/in	761 / 29.96		965 / 37.99	1040 / 40.94	1040 / 40.94	1259 / 49.56
OUTDOOR UNIT	UNIT DIMENSION	HEIGHT	mm/in	946 / 37.24	946 / 37.24		946 / 37.24	946 / 37.24	946 / 37.24
		WIDTH	mm/in	1300 / 51.18	1116 / 43.93		1300 / 51.18	1116 / 43.93	1116 / 43.93
		DEPTH	mm/in	500 / 19.68	939 / 36.96		500 / 19.68	939 / 36.96	939 / 36.96

DUCTED SPLIT MDB- BR SERIES

HEATPUMP MODEL		INDOOR UNIT		MDB300BR3	MDB350BR3		MDB400BR4	MDB500BR4	
		OUTDOOR UNIT		MMC100BR x 3	MMC100BR x 1	MMC125BR x 2	MMC100BR x 4	MMC125BR x 4	
NOMINAL COOLING CAPACITY		Btu/h		296,400	330,800		395,200	464,000	
		W		86,870	96,952		115,826	135,991	
NOMINAL HEATING CAPACITY		Btu/h		289,500	336,500		386,000	480,000	
		W		84,848	98,623		113,130	140,680	
POWER SOURCE		V/Ph/Hz		380~415 / 3 / 50			380~415 / 3 / 50		
INDOOR UNIT	UNIT DIMENSION	HEIGHT	mm/in	1231 / 48.46	1486 / 58.50		1486 / 58.50	1486 / 58.50	
		WIDTH	mm/in	1866 / 73.46	2122 / 83.54		2274 / 89.52	2274 / 89.52	
		DEPTH	mm/in	1259 / 49.56	1259 / 49.56		1526 / 60.07	1526 / 60.07	
OUTDOOR UNIT	UNIT DIMENSION	HEIGHT	mm/in	946 / 37.24			946 / 37.24		
		WIDTH	mm/in	1116 / 43.93			1116 / 43.93		
		DEPTH	mm/in	939 / 36.96			939 / 36.96		

DUCTED SPLIT MDB-ER SERIES

HEATPUMP MODEL		INDOOR UNIT	MDB 075ER	MDB100ER	MDB125ER	MDB125ER2	MDB150ER1	MDB150ER2
		OUTDOOR UNIT	MMC 075ER	MMC100ER	MMC125ER	MLC61CR2 x 2	MMC150ER	MMC 75ER x 2
NOMINAL COOLING CAPACITY		Btu/h	77,000	96,000	116,000	110,000	150,000	154,000
		W	22,570	28,140	34,000	32,240	43,960	45,130
NOMINAL HEATING CAPACITY		Btu/h	85,000	106,000	130,000	117,000	160,000	170,000
		W	24,910	31,070	38,100	34,290	46,890	49,820
POWER SOURCE		V/Ph/Hz	400/3/50		400/3/50		400/3/50	
INDOOR UNIT	UNIT DIMENSION	HEIGHT	507 / 19.96		710 / 27.95		710 / 27.95	
		WIDTH	1,507 / 59.33	1,917.2 / 75.48	1,794 / 70.63		2,073 / 81.61	
		DEPTH	904 / 35.59		1008.8 / 39.71		1,008.8 / 39.71	1,013.8 / 39.91
OUTDOOR UNIT	UNIT DIMENSION	HEIGHT	1,040.5 / 40.96		1,040.1 / 40.94	850 / 33.46	1,141.6 / 44.94	1,040.5 / 40.96
		WIDTH	981 / 38.62		1,083 / 42.63	1,115 / 43.89	1,083 / 42.63	981 / 38.62
		DEPTH	981 / 38.62		1,083 / 42.63	528 / 20.78	1,083 / 42.63	981 / 38.62

DUCTED SPLIT MDB-ER SERIES

HEATPUMP MODEL		INDOOR UNIT	MDB200ER2	MDB250ER2	MDB300ER2	MDB300ER3
		OUTDOOR UNIT	MMC100ER x 2	MMC125ER x 2	MMC150ER x 2	MMC100ER x 3
NOMINAL COOLING CAPACITY		Btu/h	192,000	232,000	300,000	288,000
		W	56,270	68,000	87,920	84,410
NOMINAL HEATING CAPACITY		Btu/h	212,000	260,000	320,000	300,000
		W	62,130	76,200	93,970	87,920
POWER SOURCE		V/Ph/Hz	400/3/50		400/3/50	400/3/50
INDOOR UNIT	UNIT DIMENSION	HEIGHT	945 / 37.20	1,291 / 50.82	1,291 / 50.82	1,546 / 60.86
		WIDTH	1,894 / 74.56	1,866 / 73.46	1,866 / 73.46	2,122 / 83.54
		DEPTH	980 / 38.58	1,199 / 47.20	1,199 / 47.20	1,199 / 47.20
OUTDOOR UNIT	UNIT DIMENSION	HEIGHT	1,040.5 / 40.96	1,040.1 / 40.94	1,141.6 / 44.94	1,040.5 / 40.96
		WIDTH	981 / 38.62	1,083 / 42.63	1,083 / 42.63	981 / 38.62
		DEPTH	981 / 38.62	1,083 / 42.63	1,083 / 42.63	981 / 38.62

DUCTED SPLIT MDB-ER SERIES

HEATPUMP MODEL		INDOOR UNIT		MDB350ER3		MDB400ER4	MDB450ER3	MDB500ER4	MDB600ER4
		OUTDOOR UNIT		MMC100ER	MMC125ER x 2	MMC100ER x 4	MMC150ER x 3	MMC125ER x 4	MMC150ER x 4
NOMINAL COOLING CAPACITY		Btu/h	328,000		384,000	450,000	464,000	600,000	
		W	96,130		112,540	131,890	135,990	175,850	
NOMINAL HEATING CAPACITY		Btu/h	366,000		424,000	480,000	520,000	640,000	
		W	107,270		124,270	140,680	152,400	187,570	
POWER SOURCE		V/Ph/Hz	400/3/50		400/3/50		400/3/50		
INDOOR UNIT	UNIT DIMENSION	HEIGHT	mm/in	1,546 / 60.86			1,546 / 60.86		1,917.8 / 75.50
		WIDTH	mm/in	2,122 / 83.54		2,274 / 89.52	2,274 / 89.52		2,274 / 89.52
		DEPTH	mm/in	1,199 / 47.20		1,466 / 57.71	1,466 / 57.71		1,965 / 77.36
OUTDOOR UNIT	UNIT DIMENSION	HEIGHT	mm/in	1,040.5 / 40.96	1,040.1 / 40.94	1,040.5 / 40.96	1,141.6 / 44.94	1,040.1 / 40.94	1,141.6 / 44.94
		WIDTH	mm/in	981 / 38.62	1,083 / 42.63	981 / 38.62	1,083 / 42.63	981 / 38.62	1,083 / 42.63
		DEPTH	mm/in	981 / 38.62	1,083 / 42.63	981 / 38.62	1,083 / 42.63	981 / 38.62	1,083 / 44.63

DOUBLE SKIN DUCTED SPLIT MDSB - B Series

COOLING ONLY MODEL		INDOOR UNIT		MDSB200B2		MDSB250B2	MDSB300B3	
		OUTDOOR UNIT		MMC100B x 2	MMC100C x 2	MMC125B x 2	MMC100B x 3	MMC100C x 3
NOMINAL CAPACITY		Btu/h	200,000		200,000	250,000	300,000	300,000
		W	58,600		58,600	73,250	87,900	87,900
POWER SOURCE		V/Ph/Hz	380~415 / 3 / 50		380~415 / 3 / 50		380~415 / 3 / 50	
INDOOR UNIT	UNIT DIMENSION	HEIGHT	mm/in	932 / 36.70		1318 / 51.90		1318 / 51.90
		WIDTH	mm/in	1972 / 70.55		1243.5 / 48.96		1243.5 / 48.96
		DEPTH	mm/in	904 / 35.60		1770 / 69.70		1770 / 69.70
OUTDOOR UNIT	UNIT DIMENSION	HEIGHT	mm/in	946 / 37.24	971.4 / 38.24	946 / 37.24	946 / 37.24	971.4 / 38.24
		WIDTH	mm/in	1116 / 43.93	1393 / 54.84	1116 / 43.93	1116 / 43.93	1393 / 54.84
		DEPTH	mm/in	939 / 36.96	500 / 19.68	939 / 36.96	939 / 36.96	500 / 19.68

DOUBLE SKIN DUCTED SPLIT MDSB - B Series

COOLING ONLY MODEL		INDOOR UNIT		MDSB350B3		MDSB400B4		MDSB500B4	
		OUTDOOR UNIT		MMC100B x 1	MMC125B x 2	MMC100B x 4	MMC100C x 4	MMC125B x 4	
NOMINAL CAPACITY		Btu/h		350,000		400,000		400,000	500,000
		W		102,550		117,200		117,200	146,500
POWER SOURCE		V/Ph/Hz		380~415 / 3 / 50					
INDOOR UNIT	UNIT DIMENSION	HEIGHT	mm/in	1557 / 61.30		1550 / 61.00		1550 / 61.00	
		WIDTH	mm/in	2050 / 80.71		2212 / 87.09		2212 / 87.09	
		DEPTH	mm/in	1153 / 45.40		1438 / 56.60		1438 / 56.60	
OUTDOOR UNIT	UNIT DIMENSION	HEIGHT	mm/in	946 / 37.24		946 / 37.24	971.4 / 38.24		946 / 37.24
		WIDTH	mm/in	1116 / 43.93		1116 / 43.93		1393 / 54.84	
		DEPTH	mm/in	939 / 36.96		939 / 36.96		500 / 19.68	

DOUBLE SKIN DUCTED SPLIT MDSB- BR SERIES

HEATPUMP MODEL		INDOOR UNIT		MDSB200BR2	MDSB250BR2	MDSB300BR3	MDSB350BR3	MDSB400BR4	MDSB500BR4
		OUTDOOR UNIT		MMC100BR x 2	MMC125BR x 2	MMC100BR x 3	MMC100BR x 1/ 125BRx2	MMC100BR x 4	MMC125BR x 4
NOMINAL COOLING CAPACITY		Btu/h		197,600	232,000	296,400	330,800	395,200	464,000
		W		57,913	67,995	86,870	96,952	115,826	135,991
NOMINAL HEATING CAPACITY		Btu/h		193,000	240,000	289,500	336,500	386,000	480,000
		W		56,565	70,340	84,848	98,623	113,130	140,680
POWER SOURCE		V/Ph/Hz		380~415 / 3 / 50					
INDOOR UNIT	UNIT DIMENSION	HEIGHT	mm/in	1015 / 39.96	1378 / 54.25		1652 / 65.03	1610 / 63.38	
		WIDTH	mm/in	1904 / 74.96	1933.7 / 76.13		2142.3 / 84.34		2320.3 / 91.35
		DEPTH	mm/in	1107.5 / 43.60	1243.5 / 48.95		1335 / 52.55		1438 / 56.61
OUTDOOR UNIT	UNIT DIMENSION	HEIGHT	mm/in	946 / 37.24			946 / 37.24		
		WIDTH	mm/in	1116 / 43.93			1116 / 43.93		
		DEPTH	mm/in	939 / 36.96			939 / 36.96		

DUCTED SPLIT MDB-D SERIES - R407C

COOLING ONLY MODEL		INDOOR UNIT		MDB075D	MDB100D	MDB125D	MDB150D1	MDB150D2	MDB200D2	
		OUTDOOR UNIT		M4MC075D	M4MC100D	M4MC125D	M4MC150D	M4MC075D x 2	M4MC100D x 2	
NOMINAL CAPACITY			Btu/h	73,000	91,000	108,000	145,000	146,000	182,000	
			W	21,395	26,670	31,653	42,497	42,790	53,500	
POWER SOURCE			V/Ph/Hz	380~415 / 3 / 50			380~415 / 3 / 50		380~415 / 3 / 50	
INDOOR UNIT	UNIT DIMENSION		HEIGHT	mm/in	507 / 19.96	507 / 19.96	710 / 27.95	710 / 27.95	710 / 27.95	881 / 34.68
			WIDTH	mm/in	1507 / 59.33	1917.2 / 75.48	1794 / 70.62	2073 / 81.61	2073 / 81.61	1324 / 52.12
			DEPTH	mm/in	904 / 35.59	904 / 35.59	964 / 37.95	964 / 37.95	964 / 37.95	1209 / 47.59
OUTDOOR UNIT	UNIT DIMENSION		HEIGHT	mm/in	1041 / 40.98	1041 / 40.98	1041 / 40.98	1142 / 44.96	1041 / 40.98	1041 / 40.98
			WIDTH	mm/in	981 / 38.62	981 / 38.62	1083 / 42.63	1083 / 42.63	981 / 38.62	981 / 38.62
			DEPTH	mm/in	981 / 38.62	981 / 38.62	1083 / 42.63	1083 / 42.63	981 / 38.62	981 / 38.62

DUCTED SPLIT MDB-D SERIES - R407C

COOLING ONLY MODEL		INDOOR UNIT		MDB250D2	MDB300D2	MDB400D4	MDB500D4	
		OUTDOOR UNIT		M4MC125D x 2	M4MC150D x 2	M4MC100D x 4	M4MC125D x 4	
NOMINAL CAPACITY			Btu/h	216,000	290,000	364,000	432,000	
			W	63,306	84,990	105,510	126,612	
POWER SOURCE			V/Ph/Hz	380~415 / 3 / 50	380~415 / 3 / 50	380~415 / 3 / 50	380~415 / 3 / 50	
INDOOR UNIT	UNIT DIMENSION		HEIGHT	mm/in	983 / 38.70	983 / 38.70	1176 / 46.29	1176 / 46.29
			WIDTH	mm/in	1486 / 58.50	1486 / 58.50	1722 / 67.79	1722 / 67.79
			DEPTH	mm/in	1298 / 51.10	1501 / 59.09	1691 / 66.57	2047 / 80.59
OUTDOOR UNIT	UNIT DIMENSION		HEIGHT	mm/in	1041 / 40.98	1142 / 44.96	1041 / 40.98	1041 / 40.98
			WIDTH	mm/in	1083 / 42.63	1083 / 42.63	981 / 38.62	1083 / 42.63
			DEPTH	mm/in	1083 / 42.63	1083 / 42.63	981 / 38.62	1083 / 42.63

DUCTED SPLIT MDB-ER SERIES - R407C

HEATPUMP MODEL		INDOOR UNIT		MDB075ER	MDB100ER	MDB125ER	MDB125ER2	MDB150ER1	MDB150ER2
		OUTDOOR UNIT		M4MC075ER	M4MC100ER	M4MC125ER	M4LC061CR x 2	M4MC150ER	M4MC075ER x 2
NOMINAL COOLING CAPACITY		Btu/h		73,000	91,000	108,000	108,000	145,000	146,000
		W		21,400	26,670	31,650	31,650	42,500	42,790
NOMINAL HEATING CAPACITY		Btu/h		81,000	109,000	124,000	112,000	150,000	162,000
		W		23,740	31,950	36,340	32,830	43,960	47,480
POWER SOURCE		V/Ph/Hz		400/3/50		400/3/50		400/3/50	
INDOOR UNIT	UNIT DIMENSION	HEIGHT	mm/in	507 / 19.96		710 / 27.95		710 / 27.95	
		WIDTH	mm/in	1,507 / 59.33	1,917.2 / 75.48	1,794 / 70.62		2,073 / 81.61	
		DEPTH	mm/in	904 / 35.59		964 / 37.95		964 / 37.95	
OUTDOOR UNIT	UNIT DIMENSION	HEIGHT	mm/in	1,041 / 40.98		1,041 / 40.98	850 / 33.46	1,142 / 44.96	1,041 / 40.98
		WIDTH	mm/in	981 / 38.62		1,083 / 42.63	1,030 / 40.55	1,083 / 42.63	981 / 38.62
		DEPTH	mm/in	981 / 38.62		1,083 / 42.63	460 / 18.11	1,083 / 42.63	981 / 38.62

DUCTED SPLIT MDB-ER SERIES - R407C

HEATPUMP MODEL		INDOOR UNIT		MDB200ER2	MDB250ER2	MDB300ER2	MDB300ER3	MDB350ER3	
		OUTDOOR UNIT		M4MC100ER x 2	M4MC125ER x 2	M4MC150ER x 2	M4MC100ER x 3	M4MC100ER	M4MC125ER x 2
NOMINAL COOLING CAPACITY		Btu/h		182,000	216,000	290,000	273,000	307,000	
		W		53,340	63,310	84,990	90,010	89,980	
NOMINAL HEATING CAPACITY		Btu/h		218,000	248,000	300,000	327,000	357,000	
		W		63,890	72,680	87,920	95,840	104,630	
POWER SOURCE		V/Ph/Hz		400/3/50		400/3/50		400/3/50	
INDOOR UNIT	UNIT DIMENSION	HEIGHT	mm/in	945 / 37.20	1,291 / 50.82	1,291 / 50.82		1,546 / 60.86	
		WIDTH	mm/in	1,894 / 74.56	1,886 / 73.46	1,866 / 73.46		2,122 / 83.54	
		DEPTH	mm/in	980 / 38.58	1,199 / 47.20	1,199 / 47.20		1,199 / 47.20	
OUTDOOR UNIT	UNIT DIMENSION	HEIGHT	mm/in	1,041 / 40.98	1,041 / 40.98	1,142 / 44.96	1,041 / 40.98	1,041 / 40.98	
		WIDTH	mm/in	981 / 38.62	1,083 / 42.63	1,083 / 42.63	981 / 38.62	981 / 38.62	1,083 / 42.63
		DEPTH	mm/in	981 / 38.62	1,083 / 42.63	1,083 / 42.63	981 / 38.62	981 / 38.62	1,083 / 42.63

DUCTED SPLIT MDB-ER SERIES - R407C

HEATPUMP MODEL		INDOOR UNIT	MDB400ER4	MDB450ER3	MDB500ER4	MDB600ER4
		OUTDOOR UNIT	M4MC100ER x 4	M4MC150ER x 3	M4MC125ER x 4	M4MC150ER x 4
NOMINAL COOLING CAPACITY	Btu/h		364,000	432,000	435,000	580,000
	W		106,680	126,610	127,490	169,990
NOMINAL HEATING CAPACITY	Btu/h		436,000	450,000	496,000	600,000
	W		127,780	131,890	145,370	175,850
POWER SOURCE		V/Ph/Hz	400/3/50		400/3/50	400/3/50
INDOOR UNIT	UNIT DIMENSION	HEIGHT	mm/in	1,546 / 60.86		1,977 / 77.83
		WIDTH	mm/in	2,274 / 89.52		2,274 / 89.52
		DEPTH	mm/in	1,466 / 57.71		1,905 / 75.00
OUTDOOR UNIT	UNIT DIMENSION	HEIGHT	mm/in	1,041 / 40.98	1,041 / 40.98	1,142 / 44.96
		WIDTH	mm/in	981 / 38.62	1,083 / 42.63	1,083 / 42.63
		DEPTH	mm/in	981 / 38.62	1,083 / 42.63	981 / 38.62